



SERIES 3 PVC SX NT

Heavy weight and flexible PVC ducting
Rigid PVC helix

*Gaine flexible lourde en PVC renforcée d'une spirale
PVC rigide noyée dans la paroi*



Structure: Flexible medium weight ducting made out of soft PVC wall, reinforced with shock-resistant PVC spiral. Smooth internal surface. Extra flexible.

Applications: Designed for suction of air, fumes and dust, cable protection, spraying in agriculture, discharging of liquids without pressure. NT version has extra chemical resistance and long flexibility properties.



Structure : Gaine flexible de poids moyen, faite d'une paroi en PVC souple renforcée d'une spirale en PVC rigide de qualité antichoc. Surface intérieure très lisse. Extra souple.

Applications : Conçue pour une utilisation d'aspiration d'air, de fumées et de poussières, pour la protection de câbles, la pulvérisation dans l'agriculture ou pour l'écoulement de liquides. La version NT résiste mieux aux produits chimiques et à la flexion répétée.

						
int mm	kg/m	mm	mm	bar	bar	m
25	0,200	0,90	45	1,80	0,60	25
30	0,240	0,90	50	1,80	0,60	25
32	0,255	1,00	50	1,80	0,60	25
38	0,310	1,00	65	1,70	0,60	25
40	0,340	1,10	80	1,70	0,55	25
45	0,420	1,10	90	1,60	0,55	25
50	0,490	1,20	100	1,60	0,55	25
60	0,620	1,20	120	1,60	0,50	25
63	0,640	1,20	120	1,40	0,50	25
70	0,760	1,20	140	1,30	0,50	25
76	0,840	1,30	150	1,20	0,45	25
80	0,880	1,30	160	1,20	0,45	25
90	1,050	1,30	180	1,10	0,45	25
100	1,170	1,40	200	1,00	0,45	25
110	1,320	1,40	220	0,85	0,45	10
120	1,500	1,40	240	0,80	0,40	10
125	1,560	1,40	250	0,75	0,40	10

Printing | Marquage :

S3 PVC SX NT n°lot

Temperature | Température :

- 25 / + 60 °C
- 13 / + 140 °F

Properties | Caractéristiques :

Extremely flexible even at low temperature.
Excellente flexibilité même à basse température.

Colors | Couleurs :

