



## FLEXACIER SUPER SPH

Phthalate-free - medium duty, steel spiral reinforced suction and delivery hose for high quality liquids and foodstuffs

*Tuyau flexible d'utilisation soutenue, de qualité alimentaire sans Phtalate, renforcé d'une spirale acier pour le pompage et le refoulement de liquides alimentaires.*



**Structure:** Flexible hose made out of soft phthalate-free food-grade PVC wall in accordance with the modified EU regulation 10/2011 (simulant A, B, C, D1) and CE 1935/2004, reinforced with steel helix coated in PVC (creating barrier against corrosion).

**Applications:** Designed for medium duty suction and delivery of high quality liquids and foodstuffs, including alcohol up to 50°. Steel spiral is coated with special formulation barrier ensuring total protection of materials transferred against corrosion.



**Structure :** Tuyau flexible fait d'une paroi PVC souple sans phtalate de qualité alimentaire selon règlement 10/2011 modifié (simulant A, B, C, D1) et CE 1935/2004, renforcé d'une spirale en acier gainée PVC (faisant office d'anti-corrosion).

**Applications :** Conçu pour une utilisation soutenue d'aspiration et de refoulement de liquides alimentaires de forte valeur ajoutée, incluant l'alcool à 50°. Le gainage de la spire garantie une protection totale contre la corrosion.

int mm	ext mm	kg/m	mm	bar	bar	m
20	30	0,350	90	7	0,90	30
25	34	0,510	100	6	0,90	30
30	37	0,680	120	5	0,90	30
32	40	0,710	140	5	0,90	30
35	45	0,770	150	5	0,90	30
38	49	0,900	160	5	0,90	30
40	52	1,130	160	5	0,95	30
50	63	1,500	190	5	0,95	30
60	73	1,730	240	5	0,90	30
70	84	2,365	280	5	0,85	30
80	94	2,700	320	5	0,85	30
90	105	3,025	360	4	0,85	30
100	123	3,340	420	3	0,80	30
120	140	5,050	500	2	0,80	20



Printing | Marquage :

FLEXACIER SUPER SPH n°lot  
 PHTHALATE FREE CE 10/2011

Temperature | Température :

- 10 / + 65 °C  
 + 14 / + 149 °F

Properties | Caractéristiques :

Smooth inside, smooth outside.  
*Lisse intérieure, lisse extérieur.*

Colors | Couleurs :

