



SANIFLEX

Light duty flexible hose for waste water disposal, with coupling

Tuyau flexible pour écoulement d'eau usée avec ses raccords









Structure: Flexible hose made out of soft PVC wall, reinforced with shock-resistant PVC spiral, external profile adapted for couplings.

Applications: Designed exhaust to waste water for deker, baths or transfer with no pressure. External calibration allows for cuffs screwing. Hose can be shaped to an «S» to be used as a siphon.



Structure : Tuyau flexible fait d'une paroi PVC souple, renforcé d'une spirale en PVC rigide de qualité antichoc, profil extérieur adapté pour une gamme d'embouts à visser.

Applications : Conçu pour une utilisation de vidange d'eau usée pour lavabo, baignoire ou de transfert sans pression. Tuyau calibré extérieur pour visser un embout. En faisant un «S» le tuyau se transforme en siphon.

 int mm	 ext mm	 kg/m	 mm	 bar	 m
25	30	190	30	-	10 - 30
30	36	240	35	-	10 - 30

Printing | Marquage :

SANIFLEX n°lot


Temperature | Température :

- 15 / + 50 °C
+ 5 / + 122 °F

Properties | Caractéristiques :

Smooth inside, corrugated outside.
Lisse intérieure, ondulé extérieur.

Colors | Couleurs :



System Système	25/32	Smooth cuff <i>embout lisse</i>	Screw ring cuff <i>embout à écrou</i>
	30/40	Smooth cuff <i>embout lisse</i>	Screw ring cuff <i>embout à écrou</i>

Cuffs | Embouts :

